

Drop Cable Clamp with Hook Datasheet

HC-A09SUV



Features

- ◆ It is suitable for flat/round fiber optic cables.
- ◆ No tools are required for installation.
- ◆ It can be adjusted by hand to provide the necessary clamping force.
- ◆ It provides effective protection for the fiber optic cable, preventing damage from wind, rain, etc.

Performances

The test methods and performances of this product material are fully compliant with the following international standards:

- ASTM A370 Standard Test Methods and Definitions for Mechanical Testing of Steel Products
- ASTM A240 Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications
- ISO 4892-3 Plastics — Methods of Exposure to Laboratory Light Sources
- ASTM D6779 Standard Classification System for and Basis of Specification for Polyamide Molding and Extrusion Materials (PA)

Specification

Body Material	PA6 (UV Resistance)
Hook Material	Stainless Steel 201
Dimension	80.5*59*17.8 mm Nominal
Hook Diameter	4 mm
Compatible Cable Range	Round Cable 2-5 mm Flat Cable 2*(3-5) mm
Breaking Load	1.0KN

Installation

Insert a drop cable of appropriate size through the main body, then place the wedge and tension the cable. Once the cable is taut, clamp it to secure the wedge in a tightened position. Finally, attach the entire assembly onto a pole bracket or hooks.

Other Model

HC-A10SUV

