

## OCC144-3F

### Fiber Optic Cross Connect Cabinet 144 Cores

#### Features

- ◆ Fotelex's cross connect cabinets have the functions of optical cable fixing, protection, optical cable termination, and optical fiber core and pigtail protection.
- ◆ With high intensity and anti-erosion performance.
- ◆ Capacity can be flexibly customized as required.
- ◆ Applicable to strap-shaped and non-strap shaped fibers, and inserting installation of SC, FC, adapters.
- ◆ Modular design, easy installation and maintenance.
- ◆ Reliable elements for fixing, splicing and earthing.
- ◆ Rubber furring are used for the connection parts between the body and the door, thus sound sealing and moisture protection achieved.



#### Technical Parameters

1	Connector Type:	SC FC
2	Atmospheric Pressure:	70kpa-106kpa
3	Relative humidity:	≤95%(40°C)
4	Operating Temperature:	-40°C~+60°C
5	Insulated Resistance:	2*10 <sup>4</sup> MQ/500v(DC)
6	Mechanical Durability Test:	≥1000 times
7	Color:	Gray

#### Specification

1	Material:	SMC
2	Dimension W*H*D(mm)	550*1030*308
3	Capacity:	144F
4	Door Type:	Single-Sided front door
5	Fiber Optical Splitter:	12*1:8 cassette PLC splitter
6	Number of Trunk Distribution Modules	1
7	Number of Branch Distribution Modules	12
8	Installation	Floor Standing

