

SPC232-SU

2×32 CASSETTE TYPE PLC SPLITTER SC/UPC

Features

- ◆ High density for efficient use of rack space in data centers or central offices
- ◆ Modular design for easy installation, maintenance, and scalability
- ◆ Low insertion loss and uniform distribution of signals for minimal signal degradation
- ◆ Wide operating temperature range for versatile deployment in various environments
- ◆ Durable and reliable construction for long-lasting performance in fiber optic networks.



General

| | |
|--------------------|-------------|
| Configuration Type | 2×32 |
| Connector | SC/UPC |
| Fiber Mode | Single-mode |
| Fiber Type | G.657A1 |
| Splitter Type | Cassette |

Dimensions

| | |
|---------------------|----------------|
| Cassette Dimensions | 130*110*100 mm |
|---------------------|----------------|

Technical

| | |
|-----------------------------|-----------------|
| Operating Temperature | -40 °C to+85 °C |
| Operating Bandwidth | 1260~1650nm |
| Insertion Loss | ≤17.5dB |
| Uniformity of Insert Loss | ≤1.8dB |
| Polarization Dependent Loss | ≤0.3dB |
| Return Loss | ≥50dB |
| Directivity | ≥55dB |

Compliance

| | |
|--------------|---------------|
| Applicable | RoHS2.0 |
| Flammability | UL94-V0 |
| Standards | IEC 61300-3-4 |

